



Rev	Drawn	Chk'd	App'd	Description	Date
P1	LF	LF	MC	First Issue	11/07/2022

Purpose of Issue
S2 - Fit for Information

Classification
Confidential

Client
**Grŵp Llandrillo Menai
 GLLM**

Project
**Welsh Sheep Centre
 Campws Glynllifon**

Drawing
Stock proof fence detail

Scale @ A3	Drawn	Checked	Approved
1:20	LF	LF	MC

Project No. **GH/006785** Date **07-06-2022**

Drawing Identifier **BS1192 Compliant**
 Project - Originator - Zone - Level - File Type - Role - Number **rev**
WSC-GLH-00-XX-DR-L-0003 **P1**



- Notes
1. All strained line wire finishing at a post shall be terminated by looping back on itself and jointed with a preformed fence connector.
 2. Intermediate posts to be set at 3.5m intervals. All joints in the spring steel wire shall be made by either a preformed fence connector or wire connector.
 3. Where the ground is undulating, ground anchors or extra intermediate posts shall be used to maintain the constant distance of the line wires from the ground.
 4. Fencing materials and workmanship to be in accordance with sections 8,10 & 11 of BS 1722 Part 2: 2006 - Specification for strained wire
 5. Stock fencing to always be located on field side, on side of attack.
 6. All dimensions are in millimetres unless otherwise stated.

Print Date: 11/07/2022 08:26:12